

# MAXIMUM LONGEVITY.

The Razor762™ is developed to have reduced gas blowback and weight savings making it a smart choice for your semi and full-auto platforms. Clocking in at 6.4", the Razor762 offers an alliance of sound suppression and length/weight savings.



### TOP FEATURES



### **Accuracy Proven**

We've sent thousands of rounds through our designs to ensure exactitude. Our vetting process gives our suppressors a proven accuracy and provides you with a repeatable zero shift when attaching/detaching your suppressor.



### **ADAPT™ Modular Technology**

Now you don't have to choose between a short rifle suppressor and a long one. With ADAPT™ Modules you get two lengths with one tax stamp. So you can have a shorter and lighter suppressor in seconds compared to months.



### **Dual Taper Locking System™**

Our quick detach mounts feature 2 tapers. The front taper provides a concentric lock up and protects the threads from carbon build up. The rear taper prevents the suppressor from loosening during firing.



### **Belt Fed Rated®**

The Razor762 is machined from top of the line materials to not only last a lifetime, but withstand any rate of fire. The Razor762 is Belt Fed Rated® and rated for calibers up to 300RUM; with no barrel length restrictions. Because we believe your gear shouldn't be what's holding you back.





## RAZOR762



# 6.4"

1.5"

### **SPECIFICATIONS**

CALIBER: 7.62mm rated to .300 RUM; Full-Auto Rated

DIAMETER: 1.5"

LENGTH:

Standard Configuration: 6.4"

WEIGHT

Standard Configuration: 15.3oz

### **MATERIALS**

Baffles: Cobalt 6

Tube: 17-4 PH Stainless Steel Mount:

17-4 PH Stainless Steel Finish: High

Temp Cerakote®

### **FEATURES**

Reduced Gas Blowback

Accuracy Comes Standard

**Dual Taper Locking System** 

Strategically Placed Engraving

Interchangeable End Caps

Belt Fed Rated®

### INCLUDES

7.62 R3 Flash Hider (5/8×24 Thread Pitch)

7.62 Front Cap

Razor762 Suppressor

Operator's Manual

Dual Taper Lock™ Mounting Instructions

Rugged Suppressors Sticker

Razor762 Sticker

### **ACCESSORIES**

### **MUZZLE DEVICES:**

M2 Brake - 5/8×24

R3 Flash Mitigation System – 7.62

R3L Flash Mitigation System - 5/8×24

R3 Flash Mitigation System - 1/2×28 (5.56)

3 Port Brake

2 Port Brake - 1/2×28 (5.56)

### **END CAPS:**

5.56 Front Cap

Flash Hider Front Cap

Ti Front Cap – 7.62mm





